



1400 HANSELMAN RD.

ANGOLA, IN 46703

260-665-7961

sales@dispatchproducts.com

www.dispatchproducts.com

FURNITURE DESCRIPTION

ELECTRIC LIFTS

THRUST 1200 N OR 800 N
MAX. SPEED 38 mm/sec
STROKE: 660 OR 604 mm
INSTALLATION DIMENSION: 560 OR 518mm, BIFMA
DUTY CYCLE: 10%

CONTROL BOX

INPUT VOLTAGE: 120 V AC 50-60 Hz
PARALLEL DRIVE: 2,3 OR 4 UNITS WITH
AUTO DETECT
POWER: 300 WATTS
ANTI COLLISION
UL APPROVED

USER CONTROL

DISPLAY OF HEIGHT
3 MEMORY POSITIONS
DIAGNOSTIC INDICATION

ATTACHED KEYBOARD SUPPORT

HEIGHT ADJUSTMENT: 17-3/4"
5-3/4" BELOW, 12" ABOVE
MONITOR SURFACE
TILT CONTROL: -15, + 9 DEG.
OPTIONAL MOTORIZED KEYBOARD
12-3/4" ADJUSTMENT
7" ABOVE, 5-3/4" BELOW
MONITOR SURFACE
TILT CONTROL: -15, +9 DEG

WRITING SURFACES

1-1/8" CORE OF MDF OR PARTICLEBOARD
45 lb DENSITY
NO ADDED FORMALDEHYDE
HIGH PRESSURE LAMINATE TOP
VAPOR PROOF UNDER LAMINATE
REPLACEABLE VINYL BUMPER

CPU CABINETS

UNDER COUNTER OR UPRIGHT
MULTIPLE ACCESS
VENTED, LOCKABLE FRONT DOORS
REMOVABLE VENTED PANELS IN REAR
(OR OPEN TO WALL OR CONNECTING
CABINET)
LOW NOISE FANS
PULL OUT SHELVES
OPTIONAL CABINET LIGHTING

ACOUSTIC WALL PANELS

37", 45" AND 53" TALL, 3" THICK, STACKABLE
AND SEGMENTED
5" BOTTOM RACEWAY UL LISTED CSA
CERTIFIED ACOUSTIC SEGMENTS NRC=.60
100 % RECYCLED FABRIC AVAILABLE
ANSI-BIFMA 5.5 COMPLIANT

PERSONAL ENVIRONMENT SYSTEM

JOHNSON CONTROLS PERSONAL ENVIRONMENT
SYSTEM
115 VAC, 3.5 amps
CONTROL OF AIR, RADIANT HEAT, BACKGROUND NOISE
AND TASK LIGHT DIMMING.
OPTIONAL FORCED AIR HEAT, 450-1800 WATTS WITH
THERMOSTAT

LIGHTING

3.7 WATT L.E.D. 115VAC, .1 AMP
50,000 HOURS RATED
30" DOUBLE ARM